

# ALO 2

## Telephone Interface



### RESUME

#### PHYSIC TELEPHONE INTERFACE, 2 LINES, ANALOG, PASSIVE

Two lines hybrid telephone interface, rack standard, to be used in radio and TV studios. Has an identical circuit of all the other ALO models and does not require the use of power supply making it easy to use. Allows the connection up to two listeners simultaneously. On the telephone line input and also on the audio inputs and outputs has RFI filters avoiding electromagnetic interference. It also has a protection against electric discharges from the telephone line that protect the equipment. Can work on conventional telephone lines or PBX extensions with variations between 20 and 50V with a minimum current of 20mA.

Balanced audio inputs and outputs with XLR connectors, isolated by transformers that guarantee high quality and immunity to noises, providing a clear and clean sound. Has audio control gain on the back panel and completely independent hybrid circuits for each listener allowing conference between them through the mix-minus on the audio console. The hybrid circuit (transformation from 2 to 4 wires) is totally electronic and active and has an adjustment for echo cancellation that provides an isolation around 50dB @ 1KHz.

On the front panel, the equipment has a ON/OFF key that attends the telephone call, a call indicator led that is on while the equipment is functioning, a return volume control to the listener and also an audio output volume control to the mixing console. Very versatile, ALO 2 is the ideal equipment to be used in transmission and recording studios in order to extract or insert quality audio on the conventional telephone line POTS.

Its case has a high standard finishing with brushed stainless steel panel.

**US (Harmonized Code):**

8517.18.0050

**WEIGHT:**

- 1,20 Kg without package;

- 1,70 Kg with package.

**DIMENTIONS (Rack standard - WxHxD):**

- 482,0 mm x 44,5 mm x 120 mm;

- 19" x 1,75" x 4,7" pol.;

**CUBAGE:**- 0,017577m<sup>3</sup>